

Spraying Machinery

PIC	NAME / MODEL	SPECIFICATION	PACKING SIZE (mm)	QUANTITY (pcs)
	200L	N.W: 70kg G.W: 82.5kg Standard Flow: 30-40L/min Matched Engine: 170F Working Pressure: 1.0-2.5Mpa Max. Range: 15M Tank Capacity: 200L	1590*690*840 Packing: 1PC/CTN	40HQ: 69 20GP: 22
	300L	N.W: 93kg G.W: 106kg Standard Flow: 30-40L/min Matched Engine: 170F Working Pressure: 1.0-2.5Mpa Max. Range: 15M Tank Capacity: 300L	1670*720*930 Packing: 1PC/CTN	40HQ: 42 20GP: 20
	IF-3WPZ-700G	Standard Power: 36.8/2400kw/r/min (50HP) Tank Capacity: 700L Working pressure: 0.2-0.5Mpa Matched Engine: Four-cylinder, Four-stroke water-cooled diesel engine Sprinkler type: Fan nozzle Spraying width: 12000mm The flow of the pump: 45-63L/min Ground clearance: 1100mm Wheelbase: 2050mm Before and after the maximum Track: 1500mm Front wheel outer Diameter: 940mm Front tire width: 120mm Rear wheel outer Diameter: 940mm Rear tire width: 120mm Tyre type: Pneumatic tire Brake form: Moisture friction brake Clutch form: Pressure plate type Driving method: Four-wheel drive Speed: 1 gear: 4.5km/h 2 gear: 7km/h 3 gear: 18km/h R gear: 4km/h	—	20GP:1