

IF-16C-1 PLUS

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 3.46KG G.W: 4.37KG Capacity: 16Liter Tank Material: PP Working Pressure: 0.2-0.4Mpa Lance: 304 Stainless Steel Side: Transparent Water Level Line Spare Parts: SPRAYER PART PUMP CYLINDER + STEEL BALL+AGITATOR, Long Rocker 800g, Hose 135cm, 304 Stainless Steel Lance, Adjustable Thick Straps, 3 Rubber Seals (1 Black, 1White and 1 Transparent Seal), 4 Nozzles (IFOURNI micro nozzles, adjustable stainless steel spray plates nozzles, conical nozzles, and fan-shaped nozzles.), Tank Filter, Cup 100ml, Mask, Gloves, Goggles, 3 Seal Rings (For lance), 1 Yellow Nozzle Tip, 3 Rocker Fixed Buckle. Color: Blue Barrel, Black Bottom Packing Size: 420*180*583mm	680	1600

STANDARD FEATURES:

Transparent Water Level Line



Hose 135cm



Accessories



Mask



Pump Cylinder + Steel Ball



304 Stainless Steel Lance



Tank Filter



Agitator



Long Rocker 800g



Adjustable Thick Straps



Goggles



Switch



Cup 100ml



Gloves



Features/Selling Points:

1. Made of PP material, the barrel has a net weight of 1.3kg, passes a 1.2m drop test when fully filled with water, and supports customizable colors.
2. The air chamber withstands a 12kg burst pressure test and includes a built-in stainless steel ball for enhanced sealing.
3. Transparent water level line with dual volume marks (liters and gallons).
4. Adjustable shoulder strap with thickened sponge padding for comfort.
5. 800g long connecting rocker with a large ergonomic curvature for effortless operation.
6. 304 stainless steel spray lance, fully fluorinated rubber switch.
7. 36g deep 10cm mesh filter with reinforced screen.
8. 135cm black rubber hose rated for 16kg pressure testing (with anti-deformation and threaded protective connectors).
9. Includes full protective gear: gloves, goggles, and an N95 mask.
10. The new agitator has been improved with the function of disassembling and assembling the cylinder screws, and four water flow holes have been added to the bottom. The agitator will stir up and down along with the movement of the air chamber, thereby increasing the flow rate of the liquid medicine.

IF-16C-1

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 3.2KG G.W: 4.05KG Capacity: 16Liter Tank Material: pp Working Pressure: 0.2-0.4Mpa Lance: Fiberglass Lance Side: Transparent Water Level Line Spare Parts: SPRAYER PART PUMP CYLINDER + STEEL BALL+AGITATOR, Long Rocker 800g, Switch, Hose 135cm, Fiberglass Lance 70cm, Adjustable Thick Straps, 3 Rubber Seals (1 Black, 1White and 1 Transparent Seal), 4 Nozzles, Tank Filter, Cup 100ml, Mask, Rubber Gloves, Goggles. Color: Blue Barrel, Yellow Bottom Packing Size: 420*180*583mm	680	1600

STANDARD FEATURES:

Transparent Water Level Line



Pump Cylinder + Steel Ball+Agitator



Long Rocker 800g



Switch



Hose 135cm



Fiberglass Lance70cm



Adjustable Thick Straps



Cup 100ml



Accessories



Tank Filter



Goggles



Gloves



Mask



Features/Selling Points:

- 1.Made of PP material, the barrel has a net weight of 1.3kg, passes a 1.2m drop test when fully filled with water, and supports customizable colors.
- 2.The air chamber withstands a 12kg burst pressure test and includes a built-in stainless steel ball for enhanced sealing.
- 3.Transparent water level line with dual volume marks (liters and gallons).
- 4.Adjustable shoulder strap with thickened sponge padding for comfort.
- 5.800g long connecting rocker with a large ergonomic curvature for effortless operation.
- 6.70cm extended-length, thickened fiberglass spray lance with O-ring grooves.
- 7.36g deep 10cm mesh filter with reinforced screen.
- 8.135cm black rubber hose rated for 12kg pressure testing.
- 9.Includes full protective gear: gloves, goggles, and an N95 mask.

IF-20C-1

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 3.2kg G.W: 4.05kg Capacity: 20L Tank Material: PP Working Pressure: 0.2-0.4Mpa Side: Transparent Water Level Line Lance: Fiberglass Lance Side: Transparent Water Level Line Spare Parts: SPRAYER PART PUMP CYLINDER + STEEL BALL+AGITATOR, Long Rocker 800g, Switch, Hose 135cm, Fiberglass Lance 70cm, Adjustable Thick Straps, 3 Rubber Seals (1 Black, 1White and 1 Transparent Seal), 4 Nozzles, Tank Filter, Cup 100ml, Mask, Rubber Gloves, Goggles. Color: Blue Barrel, Yellow Bottom Packing Size: 450*195*580mm	590	1375

STANDARD FEATURES:

Transparent Water Level Line



Hose 135cm



Accessories



Mask



Pump Cylinder + Steel Ball+Agitator



Fiberglass Lance70cm



Tank Filter



Long Rocker 800g



Adjustable Thick Straps



Goggles



Switch



Cup 100ml



Gloves



Features/Selling Points:

- 1.Made of PP material, the barrel has a net weight of 1.3kg, passes a 1.2m drop test when fully filled with water, and supports customizable colors.
- 2.The air chamber withstands a 12kg burst pressure test and includes a built-in stainless steel ball for enhanced sealing.
- 3.Transparent water level line with dual volume marks (liters and gallons).
- 4.Adjustable shoulder strap with thickened sponge padding for comfort.
- 5.800g long connecting rocker with a large ergonomic curvature for effortless operation.
- 6.70cm extended-length, thickened fiberglass spray lance with O-ring grooves.
- 7.36g deep 10cm mesh filter with reinforced screen.
- 8.135cm black rubber hose rated for 12kg pressure testing.
- 9.Includes full protective gear: gloves, goggles, and an N95 mask.

IF-16C-3

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 2.9KG G.W: 3.5KG Capacity: 16L Tank Material: pp Working Pressure: 0.2-0.4Mpa Lance: Adjustable SS Lance Spare Parts: PUMP CYLINDER + Glass Ball, Long Rocker 700g, Switch, Hose 130cm, Adjustable SS Lance, Thick Straps, 2 Rubber Seals (1 Black and 1 White), 5 Nozzles, Filter, Cup 100ml, 4 Small Rubber Rings. Color: White Barrel, Black Bottom Packing Size: 395*180*535mm	780	1820

STANDARD FEATURES:

Pump Cylinder + Glass Ball



Long Rocker 700g



Switch



Hose 130cm



Adjustable SS Lance



Thick Straps



Accessories



Filter



Cup 100ml



Features/Selling Points:

1. Made of PP material, the barrel has a net weight of 1.3kg, and supports customizable colors.
2. The air chamber withstands a 8kg burst pressure test.
3. with dual volume marks (liters and gallons).
4. Padded thickened sponge shoulder straps.
5. 700g long connecting rocker with a large ergonomic curvature for effortless operation.
6. Stainless steel telescopic spray lance, not less than 90g, 60cm in length (maximum length of 100cm).
7. 130cm black rubber hose rated for 8kg pressure testing.

IF-20C-3

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 3.0KG G.W: 3.6KG Capacity: 20L Tank Material: pp Working Pressure: 0.2-0.4Mpa Lance: Adjustable SS Lance Spare Parts: PUMP CYLINDER + Glass Ball, Long Rocker 700g, Switch, Hose 130cm, Adjustable SS Lance, Thick Straps, 2 Rubber Seals (1 Black and 1 White), 5 Nozzles, Filter, Cup 100ml, 4 Small Rubber Rings. Color: White Barrel, Black Bottom Packing Size: 410*200*535mm	650	1610

STANDARD FEATURES:

Pump Cylinder + Glass Ball



Long Rocker 700g



Switch



Hose 130cm



Adjustable SS Lance



Thick Straps



Accessories



Filter



Cup 100ml



Features/Selling Points:

1. Made of PP material, the barrel has a net weight of 1.4kg, and supports customizable colors.
2. The air chamber withstands a 8kg burst pressure test.
3. with dual volume marks (liters and gallons).
4. Padded thickened sponge shoulder straps.
5. 700g long connecting rocker with a large ergonomic curvature for effortless operation.
6. Stainless steel telescopic spray lance, not less than 90g, 60cm in length (maximum length of 100cm).
7. 130cm black rubber hose rated for 8kg pressure testing.

IF-16C-5

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 2.4KG G.W: 2.8KG Capacity: 16Liter Tank Material: pp Working Pressure: 0.2-0.4Mpa Lance: Fiberglass Lance Spare Parts: PUMP CYLINDER + Glass Ball, Long Rocker 595g, Switch, Hose 120cm, Fiberglass Lance, Thick Straps, 1 Rubber Seals (White), 3 Nozzles, Filter. Color: Blue Barrel, Yellow Bottom Packing Size: 365*180*515mm	810	2030

STANDARD FEATURES:

Pump Cylinder + Agitator



Long Rocker 595g



Switch



Hose 120cm



58cm Fiberglass Lance



Thick Straps



Accessories



Filter



Features/Selling Points:

- 1.Made of PP material, the barrel has a net weight of 1.18kg, and supports customizable colors.
- 2.The air chamber withstands a 8kg burst pressure test.
- 3.Padded thickened sponge shoulder straps.
- 4.595g long connecting rocker.

IF-16D-1

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS))
	N.W: 2.9KG G.W: 3.5KG Capacity: 16L Tank Material: PE Working Pressure: 0.2-0.4Mpa Lance: Fiberglass Lance Spare Parts: Sprayer Pump Cylinder + Glass Ball, Long Rocker 700g, Switch, Hose 130cm, 58cm Fiberglass Lance, 120cm Thick Straps, 2 Black Rubber Seals, 4 Nozzles, Filter, 100ml Cup. Color: Blue Barrel, Black Bottom Packing Size: 370*185*525mm	890	2000

STANDARD FEATURES:

Pump Cylinder + Glass Ball



Long Rocker 700g



Switch



Hose 130cm



58cm Fiberglass Lance



Thick Straps



Accessories



Filter



100ml Cup



Features/Selling Points:

- 1.Made of PE material, the barrel has a net weight of 1.3kg, passes a 1.2m drop test when fully filled with water, and is a blow-molded, one-piece construction with customizable colors.
- 2.The air chamber withstands a 12kg burst pressure test.
- 3.Extended cotton strap (120cm).
- 4.700g long connecting rocker with a large ergonomic curvature for effortless operation.
- 5.130cm black rubber hose rated for 12kg pressure testing.

IF-20D-1

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS))
	N.W: 3.3KG G.W: 3.9KG Capacity: 20L Tank Material: PE Working Pressure: 0.2-0.4Mpa Lance: Fiberglass Lance Spare Parts: Sprayer Pump Cylinder + Glass Ball, Long Rocker 700g, Switch, Hose 130cm, 58cm Fiberglass Lance, 120cm Thick Straps, 2 Black Rubber Seals, 4 Nozzles, Filter, 100ml Cup. Color: Blue Barrel, Black Bottom Packing Size: 390*195*525mm	830	1740

STANDARD FEATURES:

Pump Cylinder + Glass Ball



Long Rocker 700g



Switch



Hose 130cm



58cm Fiberglass Lance



Thick Straps



Accessories



Filter



100ml Cup



Features/Selling Points:

- 1.Made of PE material, the barrel has a net weight of 1.55kg, passes a 1.2m drop test when fully filled with water, and is a blow-molded, one-piece construction with customizable colors.
- 2.The air chamber withstands a 12kg burst pressure test.
- 3.Extended cotton strap (120cm).
- 4.700g long connecting rocker with a large ergonomic curvature for effortless operation.
- 5.130cm black rubber hose rated for 12kg pressure testing.

IF-GP15-1

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS))
	N.W: 3.2kg G. W: 3.7 kg Capacity: 15L Tank material: PP Work pressure: 0.2-0.4Mpa Lance: PP+PVC Composite Lance Spare parts: Solid Rocker 460g , Hose 140cm, PP+PVC composite lance 53cm , Adjustable Thick Straps, 4 Nozzles and Accessories, Cup 100ml ,Mask, Rubber Gloves, Goggles. Color: Yellow Tank, Blue Tank Cover Packaging size: 341 * 256 * 481mm	700	1680

STANDARD FEATURES:

Air chamber accessories 	Long Rocker 460g 	Hose 140cm 	Switch 
Thick Straps 	Filter 	53cm PP+PVC Lance 	100ml Cup 
Goggles 	Mask 	Gloves 	Accessories 

Features/Selling Points:

- 1.Made of PP material, the barrel has a net weight of 1.55kg, passes a 1.2m drop test when fully filled with water, and supports customizable colors.
- 2.Adjustable sponge shoulder strap.
- 3.53cm PP+PVC composite environmental protection material spray lance;
- 4.46g, large diameter filter;
- 5.140cm black rubber hose rated for 12kg pressure testing.
- 6.Accessories bag: double wearing parts, all-round accessories bag;
- 7.Includes full protective gear: gloves, goggles, and an N95 mask.

IF-20EI-1

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 5.2KG G.W: 5.8KG Capacity: 20L Tank Material: Thickened PE The Base Material: PP Detachable Li-ion Battery: 18V/5.2AH Pressure Pump: 2.2L/min Lance: 304 Stainless Steel Lance Charger: Different Charger Plug Provided Certificate: CE, FCC, UKCA , ROHS With Exclusive Patent of Independent Research and Development Packing Size: 410*275*560 mm	490	1100

STANDARD FEATURES:

**20L+5GAL
Double Water level line**



304 Stainless Steel Lance



Three Different Types Of Nozzles



**130CM, Withstand 16KG Pressure Hose
Connected with pump directly**



**Switch with Viton seal ring
Exclusive threaded protection joint, Effectively
Relieve The Deformation Of The Hose**



18V5.2A Quick-connect Lithium Battery



Different charger plug provided



2.2L/min Pressure Pump



**Replaceable Control Module,
with Real-time Power Indicator light**




**Specially Designed Thickened Battery Cover,
Protect the battery better**



**Concave And Convex Design Tank Cover, Non-
slip And Easy To Grasp Rubber Sealing Ring To Effectively Prevent
Liquid Leakage**



Humanized Curved Handle Multi Reinforcing Ribs more Stable and comfortable Stainless steel D-type pin is sturdy and durable 	Comfortable Multi-functional Adjustable Straps And Backrest 	Multi-function personal storage bag 	Bottom Plate With Multiple Drainage Outlets 
Features/Selling Points: 1.Made of PP and PE materials, blow-molded as a single piece with a thickened base design to prevent cracking. Customizable colors are available for customers. 2.18V, 5.2A Makita-compatible quick-connect lithium battery with a cycle life of 500 charges/discharges, retaining no less than 80% capacity. 3.2.2L energy-efficient Emc pressure pump with a lifespan twice that of conventional market products, up to 1000 hours. 4.Charger: High-quality chargers with multiple certifications, offering various plug options (EU, US, UK standards), and a 3-year warranty. 5.Full-charge usage time is twice that of conventional market products, lasting approximately 5 hours. 6.Adjustable, thickened sponge-comfort shoulder straps, S-shaped ergonomic sponge backrest, and adjustable thickened, widened waist support for enhanced comfort and reduced user fatigue. 7.Convenient small designs: Shoulder straps with switch hooks and a waist support storage bag. 8.Stainless steel D-ring pins on the shoulder straps, corrosion-resistant and slip-resistant. 9.304 stainless steel spray lance, fully fluorinated rubber switch, and 130CM black rubber hose rated for 16kg pressure testing (with anti-deformation and threaded protective connectors). 10.Modular product design for easy disassembly and maintenance. Control module features a percentage battery level indicator for clear visibility. 11.The product boasts independently developed patents and has obtained multiple certifications, including CE (Europe), FCC (USA), ROHS (Europe), and UKCA (UK).			

IF-5EU-1 ULV

PIC	NAME / MODEL	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	IF-5EU-1 (ULV)	Work Voltage(9V/DC) : 6—12V Flow Rate: 25—200ml/min Disc Speed: >=2000rpm Droplet Size: 50—150um Big Tank Volume: 5L Small Tank Volume: 1L Dry Battery: 4-8pcs Shaft Carton Size: 970*160*160 Tank Carton Size: 250*190*280	780	1800

STANDARD FEATURES:

5 nozzles with different flow rates

Joints linked 1L tank and nozzle

5L knapsack tank

1L tank



Accessories



Tube, 8.5MM ID X 11MM OD -2M, PVC



New Switch



Cup 50ml



Features/selling points:

1. The attribute is 'unique', with a small market and less competition;
2. Series circuit, each component is easy to disassemble and replace with accessories (our company can sell the complete set of accessories for the machine);
3. It can atomize the liquid medicine into tiny particles (usually 15-100 microns), and improve the coverage area and permeability (generally, spray is incomparable).
4. 4-8 dry batteries, adjustable according to demand;
5. Accessories package: N95 mask, gloves, face mask, locking clamp, self tapping screw, orange nozzle, motor small seal ring, motor large seal ring, connecting elbow, all included in the original price.
6. Efficient and energy-saving: Less dosage per unit area, saving chemicals and water resources, and reducing usage costs.
7. Lightweight design, easy to carry and operate, suitable for various environments.
8. The fog droplets are evenly distributed to ensure effective coverage of the target area by the medication.
9. Reduce drug residues and minimize environmental pollution.

IF-A036

PIC	SPECIFICATION	20GP	40HQ
	Net Weight: Standard: 10.4kg Gross Weight: Standard: 11.4kg Suitable Seeds: Wheat, corn, soybeans, peanuts, cotton, green beans, etc. Material: Push rod and duckbill are made of 201 stainless steel, press wheel is PP, transparent parts are PC, blue plastic components are ABS. Capacity: 2-3 kgs of seeds Color: IFOURNI Blue Standard Machine Configuration: 12 nozzles (can be adjusted to 7, 8, 9, or 10 nozzles) 13 seed wheels, +1 auxiliary wheel 4 types of spacers: No. 7 (7 holes), No. 8 (8 holes), No. 9 (9 holes), and No. 10 (10 holes) For 6-nozzles sowing adjustment: Remove the side panel spacer, unscrew the seed positioning screws on every other nozzle, and reinstall the spacer. Accessory Pack (includes full machine installation accessories): 4 large springs; 4 handle grips; 1 set of duckbills; 2 small duckbill springs; 4 positioning wheels (all complimentary); 4 H-rod connecting screws for press wheels (2 fully threaded, 2 half threaded); 18 push rod connecting screws; 2 sets of push rod connecting clips; 2 crescent clips. Default installed spacer packaging dimensions: 56*24*58cm Packaging dimensions without spacer: 54*24*58cm Plant Spacing: 13-25cm 6 nozzles: 25cm; 7 nozzles: 21cm; 8 nozzles: 18.5cm; 9 nozzles: 16.5cm; 10 nozzles: 14.5cm; 12 nozzles: 13cm.	380	860

STANDARD FEATURES:

1.2mm thickness 201 stainless steel handle +4mm sponge grip



Press wheel



7 Nozzles baffle plate *7



1.3mm thickness 201 stainless steel push rod



The holder can be pushed back and forth



8 Nozzles baffle plate *8



Nylon clamp wheel




9 Nozzles baffle plate *9




Galvanized iron push rod fastener



201 stainless steel nozzle



10 Nozzles baffle plate *10



Galvanized link sheet



Adjustment sheet



Luxury accessory bag



Press wheel H frame, 2.5mm thick



Sowing tray (13+1)



Features/Selling Points:

- Can withstand adult stepping without obvious damage.
- 1.3mm thickened stainless steel push rod, fully welded, rust-proof and durable.
- Sponge handle for comfortable use.
- Galvanized iron push rod connecting plate.
- 201 stainless steel duckbill, rust-proof and resistant to deformation.
- Galvanized iron push rod connecting buckle.
- Wear-resistant nylon positioning wheel.
- 13 sets of seeding plates, suitable for most seed types.
- Premium accessory pack; complete accessories for easy replacement.

IF-3WB-900

PIC	SPECIFICATION	20GP QUANTITY (PCS)	40HQ QUANTITY (PCS)
	N.W: 10KG G.W:12.4 KG Fan Rotation Speed: 7500r/min Tank Capacity: 14L Range: ≥12M Matched power: 1E40F-5A Standard Power: 1.25kw Mixed Fuel Ratio: 25:1/30:1 Packing Size: 440*360*655	270	655

STANDARD FEATURES:

14L Liquid Tank



1L Fuel Tank



Engin



Effuser



Engine Shell



Thick Straps



Switch



Carburetor



Accessories



Tank Filter



Thickened sponge backrest



Features/Selling Points:

1. Lifespan of gasoline engine: Continuous operation for no less than 120 hours. The trial period in the market is also more than twice as long (market-leading 50 hours, general products 30-40 hours).
2. Engine housing material: Nylon PA6 + 30% glass fiber. Market standard PP. Advantages: Good toughness, resistance to aging, corrosion resistance, impact resistance, wear resistance, high temperature resistance. The deformation resistance is three times that of pure PA6; The heat deformation temperature is increased by more than 200 degrees.
3. 100% pressure test of fuel tank: The fuel tank cover only allows air intake but no leakage, ensuring the sealing effect of the fuel tank. The lengthened fuel suction pipe and wool filter reduce the intake of gasoline impurities.
4. Starter lifespan: More than 10,000 times.
5. Adjustable and thickened safety sponge strap: Can be disassembled with one click, ensuring safe use.